

4G Router With Battery Backup

Model: HC-CPF903



Simple Introduction

The HC-CPF903 use MTK solution, one 10/100Mbps WAN/LAN port, one USB port accept powering in, one SIM card slot, 2.4G Wifi rate up to 150mbps, with LCD screen to shows operation information, support WAN to LAN and wifi, 4G to LAN and Wifi, 3000mAh battery as optional.


Product Feature

- Support 802.11n/b/g network protocol, the max transmission rate could be 2.4G 150Mbps
- Support 802.11.3/802.3U protocol, 1* 10/100Mbps Auto MDI/MDIX WAN/LAN Port
- 4 external antennas, 2pcs wifi antennas, 2pcs lte antennas
- LCD screen to show different operation
- Removable 3000mAh battery as optional
- Default 1 SIM card slot, support 2 SIM card slots as optional but it is can not be common using with 3000mAh battery
- Preload English system, easy setting web

Product Datasheet

Hardware Platform	HW_VER	HC-CPF903			
	MTK Chipset	MT6735WM			
	RAM/ROM	4GByte EMMC+512MByte DDR2			
	Band	FDD LTE: B1,B3,B5,B7,B8,B20	TDD LTE: B38,B39,B40,B41	WCDMA: B1,B5,B8	GSM: 900/1800Mhz

	3GPP	3GPP R9 Cat.4	3GPP R9 Cat.4	3GPP R7&R8 HSDPA Cat.24(64QAM) HSUPA Cat.7(16QAM)	3GPP2
	Transfer rate	up to 150Mbps DL up to 50Mbps UL	up to 150Mbps DL up to 50Mbps UL	HSDPA up to 42.2Mbps DL HSUPA up to 11.5Mbps UL	3.1Mbps DL
	Wi-Fi Chipset	MT6625L			
	Wi-Fi	IEEE 802.11b/g/n			
	Wi-Fi rate	up to 150Mbps			
	Encryption	Wi-Fi Protected Access™ (WPA/WPA2)			
	Antenna	2pcs*2.4G Wifi antennas, 2pcs* LTE antennas			
Customization		Smart system, strong customization ability			
Display	LCD	Color display			
	LED	LED			
Port	Button	1 Power on/off button, 1 Reset button			
	SIM slot	1 SIM slot, 2 SIM slot as optional(battery and 2 sim slots can't be together)			
	USB port	USB TYPE A (5V 1A IN)			
	DC	12V 1A IN			
	RJ45	1* WAN/LAN port			
	Battery	3000mAh, 6-8hours working time			PS. The battery does not support hot-plug
Internet	Wi-Fi	Wi-Fi AP, Max 10 users			
	SSID	4G-CPE-XXXX (last 4 digits of the IMEI number)			
	WIFI password	1234567890			
Operating Environment	Working temperature	-10°C to 65°C			
	Working height	Current tested max height 3000m (10,000 inches)			
	Operation system	PC Users: A PC with Windows XP (SP3), Windows Vista (SP1), Windows 7, or Windows 8 WIN10	MAC Users: A Mac with OS X v10.5.7, OS X Lion v10.7.3 or later	IPAD Uers: An iPhone, iPad, or iPod touch with iOS 5 or later	Android Uers: An mobile Phone or Tablet PC with Android 2.3 or later
	Operation Browser	Internet Explorer 8.0 ,Mozilla Firefox 40.0 ,Google Chrome 40.0 ,Safari or above			

Software Platform	System	Android 6.0
WEB	Gateway	http://192.168.199.1
	Log in	Password: admin (password modification requested to done at first logging as default setting Language(Chinese/English)
	Status	Connection; APN;IP; Signal Strength; Battery Capacity; Conneting time; Users
	Networks	APN configuration: International roaming switch, APN, User name, Password, Authorization type modification, New APN, Restore default APN parameters. Traffic statistics: Traffic Limitation: Afering reaching the set value, limit the speed as set.
	Wifi	WLAN configuration: SSID modification, encryption methods, encryption password, Maximum user number setting, support PBC-WPS WiFi connection list: check the list that connect to this device, check MAC address, IP address, hostname, forbid and recover access to internet.
	Ethernet mode	
	System Manage	Login password management: User name, password modification System operation: Restart, Shutdown, Restore factory setting System Information: Check software version, WLAN MAC address, IMEI NO. Phonebook setting: New, modify, look up, delete contact GPS control: GPS function turn on/off
	SMS Management	SMS create, delete, send